

HILD - Unheated Drum Insulating Lid - data sheet

Area of application

The Unheated Drum Insulation Lid HILD is the perfect addition for all drum heater types HISD, HTSD and HSHP and fits all steel and plastic drums with a 200 or 220 l volume. The low priced and heavy-duty lid does not only reduce energy losses but also shortens the heating up process. Possible heat losses on top of the drum are reduced to a minimum.

The drum insulation is available in two different materials. Depending on the drum heater in use you can choose between silicone-coated glass fibre and PTFE material.



Technical data

Max. temperature of insulation	220 °C
Outer material	Silicone-coated glass fibre, resp. PTFE
Insulation material	Glass fibre
Protection class	-
Cable length	-
Type of cable	-
Fastening	-
Control	-
Control range	-
Heating zones	-
Special sizes possible	-

Drum size	Outer material	Power at 230 V	Ø	Part-No.
200 / 220 (for HISD / HTSD)	Silicone-coated glass fibre	-	appr. 600 mm	387R.006
200 / 220 (for HSHP)	PTFE	-	appr. 600 mm	387R.017

Contact

Friedr. Freek GmbH
Sudetenstraße 9
58708 Menden
Tel.: +49 2373 9590 0
Fax.: +49 2373 9590 30

freek-fassheizungen.de



Download our contact details on your smart phone. Just scan the code with your QR-Reader-App.