

IBC/B - Container Jacket Heater (up to 90 °C) - data sheet

Area of application

The IBC/B-Container Jacket Heater is an insulated heater jacket for the heating of bottle-in-a-cage containers. All four sides of the container are covered by the heater. The heater has two separate heating circuits (top and bottom), allowing for an economical heating of half-filled containers, too. An unheated insulating lid can be used in addition to reduce the heat-up time.



Technical Data

Max. temperature of insulation	90 °C
Outer material	Flame retardant waterproof polyurethane-coated polyester
Insulation material	Fibreglass
Protection class	II
Cable length	4 meters
Type of cable	H07RN-F with Schuko-plug
Fastening	Quick-release buckles
Control	2 Capillary pipe thermostats
Control range	0 – 90 °C (or 0 – 40 °C)
Heating zones	2
Special sizes possible	yes

Container size	Power at 230 V	Length	Width	Part-No.
1000 liters	2 x 1000 W	4400 mm	1000 mm	387K.003

Operational safety

All IBC/B-Container Jacket Heater correspond to the EMV low-voltage guideline valid within the EU and are marked accordingly with the CE sign.

The electricity supply should be separated from the container heater if the container is empty, during the filling process, or during installation and disassembly of the heater itself. The device should only be used in dry surroundings and with a ventilated container to avoid pressure building up inside the container.

Contact

Friedr. Freek GmbH
Sudetenstraße 9
58708 Menden
Tel.: +49 2373 9590 0
Fax.: +49 2373 9590 30

freek-fasheizungen.de



Download our contact details on your smart phone. Just scan the code with your QR-Reader-App.